




# SHACMAN

## L3000 4X2 CARGO TRUCK

Main Specifications

| Model                     |                     | SHACMAN SX11858J501   |  |
|---------------------------|---------------------|---|--|
| GVW (kg)                  |                     | 18000   |  |
| Curb mass (kg)            |                     | 5900  |  |
| Max Loading capacity (kg) |                     | 12100   |  |
| Dimensions (mm)           | Length              | 8940  |  |
|                           | Width               | 2470  |  |
|                           | Height              | 3050  |  |
| Wheel base (mm)           |                     | 5000  |  |
| Front/Rear Overhang       |                     | 1340/2600   |  |
| Emission Standards        |                     | EuroII  |  |
| The max speed (Km/h)      |                     | 90  |  |
| Engine                    | Model               | WEICHAI WP6.210E32  |  |
|                           | Max power (Kw/rpm)  | 155/2300  |  |
|                           | Max torque(n.m/rpm) | 800N.m/1400-1600  |  |
|                           | Type                | Diesel 6-cylinder in line, 4-stroke, water cooling, with turbo charging and inter-cooling |  |
|                           | Displacement (L)    | 6.75  |  |
| Gearbox                   | Transmission        | FAST 8JS85TE-C Aluminum with PTO  |  |
|                           | Type                | Manual  |  |
|                           | Speed               | 8F&2R   |  |
|                           | Ratio               | F: 10.36/6.48/4.32/3.47/2.40/1.5/1.00/0.8<br>R: 10.53/2.44                                |  |
| Steering                  |                     | Chinese brand Left hand Drive.  |  |
| Clutch                    |                     | φ395  |  |
| Cab                       |                     | SHACMAN L3000 cab with deflector  |  |

|                        |                 |  |
|------------------------|-----------------|--|
|                        |                 | Driver seat with hydraulic   |
|                        |                 | ONE sleeping bed   |
|                        |                 | The third seat   |
| Air filter             |                 | General Air filter   |
| Air-conditioner        |                 | Automatic A/C  |
| Front axle             |                 | 4.8T with disk brake   |
| Suspension             |                 | Front& Rear Multi-leaf spring  |
| Frame (mm)             |                 | 870x250 (7+4)  |
| Rear axle              |                 | 10T MAN technology single reduction driving axle with inter-wheel differential and differential lock. Ratio: 4.625   |
| Brake System           | Type            | Front disk rear drum   |
|                        | Auxiliary Brake | WEVB 4 channels ABS  |
| Tire                   |                 | 10.00R20 with one spare tire   |
| Battery                |                 | 24V, 135Ah   |
| Fuel tank capacity (L) |                 | 300L Aluminum Tank with cover  |
| Color                  |                 | White  |
| Equipment              |                 | Electric flip cab, Electric window shaker, Central locking (with remote control), Electric heating mirror, WBCO Valves, Speed limit device, Tachograph, Electronic cruising device, Radio with MP3 |
| Cargo                  | Dimension (mm)  | 6800*2450*600  |
|                        | Thickness       | Bottom 3 mm, side 2 mm   |

|     |            |
|-----|------------|
| 发动机 | WP6.210E32 |
| X   | 927.6      |
| Y   | 251        |
| Z   | -104.4     |
| 角度  | 2° 30'     |

